

## GV 3,3 M plus



### Dotación de serie:

- 5.409.0256 Manguera flexible 3 m



- 3.753.0111



- 3.754.0228



- 3.754.0229



- 3.754.0235



- 3.754.0250



- 3.754.0230



- 6.405.0207



- 6.402.0096



- 3.754.0234



- 6.402.0095



- 3.099.0126



### Equipado con:

- Vapor saturado con presión de 9 bar, con una temperatura de 175 °C
- Mando de baja tensión en pistola
- Fabricado en acero inoxidable AISI 304
- Boiler 3,3 kW S/S AISI 304. Thickness 25/10
- Fase completa de encendido y activación: 7 min
- Regulación vapor
- Válvula de descarga
- Manómetro
- Dispositivo para utilizar productos químicos y detergentes mezclados con vapor de agua
- La caldera se puede rellenar desde el depósito (servicio continuo)
- Ruedas idóneas para su uso en ambientes alimentarios.

### GV 3,3 M PLUS

Código	8.450.0010
Presión/temperatura max.	9 bar / 175° C
Potencia absorbida caldera/tensión	3.3 kW / 230V ~ 50Hz (Ph 1)
Salida de vapor	4.62 kg/h
Tipo de caldera/capacidad	Inox AISI 304 / 4 l
Capacidad depósito agua/detergente	5 l / 5 l